



999.00 EUR

incl. 19% VAT, plus [shipping](#)



The HBFHP792X series is a ruggedized fanless automation PC. The DIN-rail mounting form factor is suitable to be used in control cabinet for industrial automation application. There are four models that can choose according to IO requirements.

|                | HBFHP792L-2807-G                                                                                                                                                                   | HBFHP792G-2807-G                                     | HBFHP792C-2807-G                                      | HBFHP792U-2807-G                                           |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|-------------------------------------------------------|------------------------------------------------------------|
| Part No        | – HBFHP792L-2807-G<br>– HBFHP792LW-2807-G<br>(WIFI)                                                                                                                                | – HBFHP792G-2807-G)<br>– HBFHP792GW-2807-G<br>(WIFI) | – HBFHP792C-2807-G<br>– HBFHP792CW-2807-G<br>(WIFI)   | – HBFHP792U-2807-G<br>– HBFHP792UW-2807-G<br>(WIFI)        |
| CPU/Chipset    | – Intel® Bay Trail N2807 Processor                                                                                                                                                 |                                                      |                                                       |                                                            |
| Memory         | – 2GB DDR3L-1333 on board memory                                                                                                                                                   |                                                      |                                                       |                                                            |
| Storage        | – 1 * full-size Mini-PCIe slot (for MSATA)                                                                                                                                         |                                                      |                                                       |                                                            |
| Network        | – 2 * Intel® GbE (MB / Intel i210IT)                                                                                                                                               |                                                      |                                                       |                                                            |
| Expansion slot | – 1 * M.2-2230 slot (for WiFi expansion)<br>WiFi card – Support IEEE 802.11a/b/g/n/ac Wireless LAN 2T2R and Bluetooth 4.2<br>– Support 802.11ac 2x2, Wave-2 compliant with MU-MIMO |                                                      |                                                       |                                                            |
| Standard I/O   | – 1 * Power button , 1 * Power LED , 1 * HDD LED<br>– 1 * USB 3.0 , 1 * USB 2.0<br>– 1 * VGA , 2 * RJ45 (support WOL)<br>– 1 * DC-In jack (Lock type)                              |                                                      |                                                       |                                                            |
| Expansion I/O  | HBFHP792L-2807-G                                                                                                                                                                   | HBFHP792G-2807-G                                     | HBFHP792C-2807-G                                      | HBFHP792U-2807-G                                           |
|                | – 4 * RJ45 , 1 * RS232(RJ45<br>TYPE)                                                                                                                                               | – GPIO (input – 16 PIN / output<br>– 16 PIN)         | – COM 1 ~ 2 / RS232(RS422 /<br>RS485) , COM 3 / RS232 | – 2 * USB 3.0 , 4 * USB 2.0 , 1<br>* RS232 (RS422 / RS485) |
| Power Source   | – FSP AC 90~240V to DC Adapter / DC12V-3.3A-40W / LV6                                                                                                                              |                                                      |                                                       |                                                            |
| Compliance     | – CE, FCC, LVD, RoHS                                                                                                                                                               |                                                      |                                                       |                                                            |
| Temperature    | – Recommended Operating Temperature: 0 ~ 50° C<br>– Working environment temperature: -20 ~ 70° C<br>– Storage Temperature: -20 ~ 70° C                                             |                                                      |                                                       |                                                            |
| Dimensions     | – 63 (W) x 89 (D) x 149 (H) mm                                                                                                                                                     |                                                      |                                                       |                                                            |
| Packing        | – Net Weight: 1.5KG<br>– Gross Weight: 2.2KG<br>– Color Box dimension: 152 (W) * 162 (D) * 260 (H) mm                                                                              |                                                      |                                                       |                                                            |
| OS Support     | – Windows 7, Windows 8.1, Windows 10, Linux                                                                                                                                        |                                                      |                                                       |                                                            |
| Warranty       | – 2 Year limited warranty                                                                                                                                                          |                                                      |                                                       |                                                            |