

698.00 EUR

incl. 19% VAT, plus [shipping](#)



- Intel Comet Lake-S !
- Q470 Chipset !
- 19" Enclosure !

Support:  [Datasheet](#)

- Intel® 10th LGA1200 Socket Comet Lake-S Processor (Max. 65W TDP)
- Support 2\* DDR4 2666/2400MHz SO-DIMM up to 32 GB
- 6\* USB3.1, 2\* USB2.0, 2\* COM, 2\* HDMI, 1\* DP, 2\* RJ45, 1\* MIC, 1\* Line out, 1\* LineIn
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 250W FLEX Power

|                |                                                                                                                                                                                                                                                                                                           |                      |  |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|--|
| Dimensions     | – 330 (W) x 192 (D) x 44 (H) mm                                                                                                                                                                                                                                                                           |                      |  |
| MB model       | – MI92-10 / Mini ITX (6.7-in * 6.7-in, 170 * 170mm)                                                                                                                                                                                                                                                       |                      |  |
| Part No        | Non-Wifi                                                                                                                                                                                                                                                                                                  | Wifi                 |  |
|                | – HBJC150I92-Q470-B                                                                                                                                                                                                                                                                                       | – HBJC150I92I-Q470-B |  |
| CPU/Chipset    | – Intel® 10th LGA 1200 Socket Core i7/i5/i3/Pentium/Celeron Processor (Max. 65W TDP)<br>– Q470 chipset                                                                                                                                                                                                    |                      |  |
| BIOS           | – AMI Flash ROM                                                                                                                                                                                                                                                                                           |                      |  |
| Memory         | – 2* Dual CH non-ECC DDR4 2666/2400MHz SDRAM SO-DIMM up to 32GB                                                                                                                                                                                                                                           |                      |  |
| Network        | – 1 * Intel i219LM<br>– 1 * Intel i211AT GbE                                                                                                                                                                                                                                                              |                      |  |
| Storage        | – 2 * 2.5" or 1 * 3.5" SATA3 6Gb/s internal drive bay<br>– 1 * M.2_SSD (M key-2242/2280) support NVMe                                                                                                                                                                                                     |                      |  |
| Expansion      | – 1* M.2 E-key 2230 (PCIex1/USB2.0) support CNVi<br>– Support onboard TPM2.0 (MI92-12) / optional                                                                                                                                                                                                         |                      |  |
| Rear I/O Port  | – 4 * USB3.1 (Gen. 2)<br>– 2 * USB3.1 (Gen. 1)<br>– 2 * HDMI 1.4 (Max Resolution: 4096×2160@30Hz)<br>– 1 * DP (Max Resolution: 4096×2304@60Hz)<br>– 2 * RJ45 (1 * Intel i219LM, 1 * Intel i211AT GbE)<br>– 1 * MIC, 1 * Line in, 1 * Line out<br>– 2 * COM (COM 1/2 support RS232/422/485)<br>– AC-in CON |                      |  |
| Front I/O Port | – 1 * Power button, 1 * Reset button<br>– 1 * Power LED, 1 * HDD LED<br>– 2 * USB2.0                                                                                                                                                                                                                      |                      |  |

|               |                                                                                                                                                                                           |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power Source  | <ul style="list-style-type: none"> <li>– 1U 250W FLEX POWER</li> <li>– AC 90~240V input</li> </ul>                                                                                        |
| Certification | – CE, FCC, LVD, RoHS                                                                                                                                                                      |
| Environment   | <ul style="list-style-type: none"> <li>– Operating Temperature : 0°C~50°C</li> <li>– Storage Temperature : -10°C~70°C</li> <li>– Humidity: 10% ~ 90% RH @40°C (non-condensing)</li> </ul> |
| Packing       | <ul style="list-style-type: none"> <li>– Net Weight■3.5 KG</li> <li>– Gross Weight■4.5 KG</li> <li>– Color Box Dimension■560(W) x 400(D) x 140(H) mm</li> </ul>                           |